

# 6.5 x 39 mm (6.5 mm GRENDEL), AP HC

# Rifle ammunition

- This cartridge is intended for use against personnel and light armored targets in 6,5 x 39 mm (6,5 mm Grendel) mm caliber weapons at distance 800 m
- The cartridges shall function within the temperature range from 54  $^{\circ}$ C to + 52  $^{\circ}$ C
- Life 10 years
- Cartridge dimensions are in accordance with Serbian military defense standard

# TECHNICAL DATA:

### **CARTRIDGE**

· Weight 17,8 g Length max 57 mm Extract force min 250 N

 Primer small rifle primer, noncorrosive, no mercuric, nontoxic

 Powder double base powder

# **CASE**

 Type 6.5 x 39 mm (6.5 mm Grendel), Boxer

 Weight approx. 7,9 g Length max 38,60 mm Material Brass CuZn30

## **BULLET**

FMJ BT AP (Full Metal Jacket Armor Piercing) Type

 Weight approx. 7,80 g (120 gr)

 Length max 30,2 mm Diameter max 6,71 mm

 Material Jacket: Gilding metal, Core: tungsten core

Ballistic coefficient G1 0.540

#### **PERFORMANCE**

 Velocity V<sub>25m</sub>  $740 \pm 10 \text{ m/s}$  Muzzle energy E<sub>25m</sub> 2135 J

 Chamber pressure max 3650 bar, EPVAT method of measurement

max extreme spread (5 shots) 220 mm at 300 m form muzzle Accuracy

 Terminal ballistic projectile penetrate 8 mm thick hard steel plate with 90 % probability -at range of 100 m

specification are defined for each contract individually

from muzzle

· Test barrel length 415 m

#### **PACKING:**

810 rds in metal box M2A1



